Huawei Fast Track Promotion

July 2021





Fast Track Promotion Application Scope

Purpose

- 1. Improve channel-driven partner sales through better commercial and quick shipment.
- 2. Use programs to shorten the processing speed of small and medium orders and strengthen the sales operation of small and medium transactions.

Application Scope

- 1. Rep offices in the West European region: Germany, France, Switzerland, Spain, Italy, and multiple countries in the West European region (Netherlands, Portugal, Belgium, Luxembourg, and Ireland).
- 2. The program is valid from July 30, 2021 to October 31, 2021. The approved draft within the validity period must be POs completed within three months.
- 3. Only specified models participate in promotion, trade factor 1.07 is required for DDP orders
- 4. If the amount of a single PO is greater than US\$200K, the distributor shall submit the PO for approval through the channel manager of the rep office.
- 5. Huawei has the right to reject a single PO or terminate this promotion program unilaterally.
- 6. No return is allowed unless the product quality is defective. Equipment with quality issues must be handled in accordance with the DOA process or Return Material Authorization (RMA) agreement.

Fast Track Promotion Content – Switch Plus WiFi6

Promotion Key Messages


- Ready to Ship, Order Today Get The Equipment JUST in 2 weeks
- On Sale: Not Only Fast Delivery, But Also Great Discount
- Switches and WiFi 6 AP Are Covered

Model	Description		
AirEngine5761-21	AirEngine5761-21 (11ax,2+4 dual radio, smart antenna, USB, BLE)		
AirEngine5761-11	AirEngine5761-11 (11ax,2+2 dual radio, smart antenna, USB, BLE)		
S6730-H24X6C	S6730-H24X6C (24个10 GE SFP+,6 * 100GE/40GE QSFP28)		
S5735-L8P4S-A1	S5735-L8P4S-A1 (8*10/100/1000BASE-T Ethernet Interface, 4*GE SFP+,PoE+,AC)		
S5735-L24P4X-A1	S5735-L24P4X-A1 (24*10/100/1000BASE-T Ethernet Interface, 4*10 GE SFP+,PoE+,AC)		
S5735-L48P4X-A1	S5735-L48P4X-A1 (48*10/100/1000BASE-T Ethernet Interface, 4*10 GE SFP+,PoE+,AC)		
Opticals	GE, 10GE, 40GE (Please refer to the BOQ for detail)		
License	N1, SNS, TBL license applied		

Can be managed by Cloudcampus: On-Premise, Cloud, Ideal for SMBs

- Access+Core 2 Layer Network
- Access Control for Wired and WLAN











AirEngine5761-11/AirEngine5761-21


- Between access and core layers: The backbone link supports 10GE link.
- Dual-link bonding increases uplink bandwidth.

High-performance core switch



CloudEngine S6730-H

- 10GE/25GE/40GE/100GE
- Native AC, managing up to 1K APs
- · Pluggable dual power slots
- 220 mm deep for flexible installation and deployment
- Wired and wireless convergence, simplified network and user management
- Telemetry-based network fault locating in minutes





Typical Scenario

Retail Store



Branch Office

Simplified gigabit access switch



CloudEngine S5735-L

8/24/48 x GE downlinks, 4 x GE SFP or 10GE SFP+ uplinks

- SVF, enabling plug-and-play
- Intelligent port hibernation and fan speed adjustment for energy saving
- Fast/Perpetual PoE, providing reliable power supply and access for PDs







Clinic



SMB

Indoor Mid-Range Wi-Fi 6 AP: AirEngine 5761-21





AirEngine 5761-21



Parameter	Specifications	Parameter	Specifications
Maximum rate	5.375 Gbit/s (0.575Gbps+4.8Gbps)	Antenna	Built-in smart antenna
Interface	2 x GE electrical port	Bluetooth	Bluetooth 5.0
Power consumption	17.9 W (excluding USB)	USB	One
Power supply	DC:12V±10%; PoE+ power supply	loT expansion	USB extended external IoT

Indoor Economical Wi-Fi 6 AP: AirEngine 5761-11





AirEngine 5761-11




Parameter	Specifications	Parameter	Specifications
Maximum rate	1.775 Gbit/s (0.575Gbps+1.2Gbps)	Antenna	Built-in smart antenna
Interface	1 x GE electrical port	Bluetooth	Bluetooth 5.0
Power consumption	15.3 W (excluding USB)	USB	One
Power supply	DC:12V±10%; PoE+ power supply	loT expansion	USB extended external IoT


CloudEngine S6730-H: Full-function 10GE routing switch

Stack bandwidth: MAC address: 384K 1.2Tbps 24 x 10GE optical ports, and 6 x 40GE/100GE optical ports VIVI VIVI VIVI VIV Cloud √ iStack √ SVF √ VXLAN √ iPCA √ ECA √ NetStream √ MPLS √ Telemetry mgmt. Native AC, managing a maximum of 1K APs SVF parent/client mode, simplified deployment and management VXLAN-based automatic virtual network deployment, Supports IEEE 1588v2 protocol to achieve preHiSec implementing multi-purpose network Insighte time synchronization.

CloudEngine S5735-L48P4X-A1: Simplified GE POE+ Access Switch




CloudEngine S5735-L24P4X-A1: Simplified GE POE+ Access Switch



Order Hardware

1) Shopping on SCT, first add the hardware you are going to order, and use the promotion discount



If you need to order Cloudcampus/Campusinsight License, please refer to next slides.

