Fujitsu recommends Windows 10 Pro.



Data Sheet FUJITSU Notebook LIFEBOOK U758

Ultra-Mobile Meets Ultra Secure

The new LIFEBOOK U758, based on the 8th generation Intel® Core™ processor is a slim and light ultra-mobile notebook for business professionals supporting ergonomics in the office. With its 39.6 cm (15.6-inch) and light weight of only 1.72 kg (3.79 lbs.) it provides excellent mobility. Ergonomic viewing is guaranteed with the anti-glare HD, FHD or optional FHD touch display options and the embedded palm vein or finger print sensor provide outstanding security. Smart design combines legacy interfaces like full-size VGA and easy upgradeability with a thin and durable housing. The common port replicator of the LIFEBOOK U family facilitates workplace sharing within today's modern workstyle.

Convenient upgradeability

Direct access to key components reduces upgrade time and costs

■ Battery, memory and internal storage can be changed easily

Family concept

Reduce your acquisition cost as well as the complexity of your IT equipment

 Shared components such as the same classic or USB Type-C port replicator, AC Adapter, keyboard layout, BIOS and bit image across the ultra-mobile LIFEBOOK U family

Elegant design and mobility

Manage your workday with premium notebooks providing ultimate convenience to maximize your productivity

■ A remarkable slim 19.2 mm ultra-mobile notebook starting from 1.72 kg, HD or FHD display, anti-glare, FHD touch panel option, aluminum/magnesium housing, optional backlit keyboard and num pad

Excellent security for your business

Enhance your security with outstanding features to best protect your notebook and company data from unauthorized access

 Embedded palm vein or finger print sensor, Trusted Platform Module 2.0, integrated SmartCard reader

Premium connectivity

Stay flexible and productive within a modern Workplace environment

- Full set of interfaces with, full-size LAN connector, full-size VGA port and USB Type-C
- Embedded 4G/LTE, WLAN and Bluetooth







Components

Base unit	LIFEBOOK U758
Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Processor	Intel® Core™ i7-8650U processor (1.9 GHz, up to 3.9 GHz, 8 MB)
	Intel® Core™ i7-8550U processor (1.8 GHz, up to 3.7 GHz, 8 MB)
	Intel® Core™ i5-8350U processor (1.7 GHz, up to 3.6 GHz, 6 MB)
	Intel® Core™ i5-8250U processor (1.6 GHz, up to 3.4 GHz, 6 MB)
	Intel® Core™ i5-7300U processor (2.6 GHz, up to 3.5 GHz, 3 MB)
	Intel® Core™ i5-7200U processor (2.5 GHz, up to 3.1 GHz, 3 MB)
	*Processor only for retail, SMB, education and government
Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM
,	8 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM
	16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM
Hard disk drives (internal)	SSD SATA III, 1024 GB M.2 module, OPAL capable
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	SSD SATA III, 512 GB M.2 module, OPAL capable
	SSD SATA III, 256 GB M.2 module, OPAL capable
	SSD SATA III, 256 GB M.2 module
	PCIe-SSD, 1024 GB M.2 NVMe module, SED
	PCIe-SSD, 512 GB M.2 NVMe module, SED
	PCIe-SSD, 256 GB M.2 NVMe module, SED
	HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
	HDD SATA III, 5,400 rpm, 1 TB, 2.5-inch, S.M.A.R.T.
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	Accessible capacity may vary, also depending on used software.
	Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe
	If configured with an HDD, the drive has an integrated shock sensor.
Interface add on cards/components (optional)	
3G/4G (optional)	LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s)
	LTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s)
WLAN (optional)	Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2
Display	39.6 cm (15.6-inch),LED backlight,(UHD/4K),Anti-glare IPS display,magnesium,3,840 x 2,160 pixel,700:1,300 cd/m²
	39.6 cm (15.6-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,350:1,220 cd/m²
	39.6 cm (15.6-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd m ²
	39.6 cm (15.6-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m²
Multimedia	
Camera	Optional: Built-in webcam, HD (Microsoft® Lync™)

Base unit

Page 2 / 6 www.fujitsu.com/fts/mobile

Raco unit	LIFEBOOK U758
Base unit	LII LUUUN U7 JU
General system information	
Processor	Intel® Core™ processor
	()
Chipset	Integrated
Supported capacity RAM (max.)	32 GB
Memory slots	2 SO DIMM (DDR4, 2400 MHz)
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS version	UEFI Specification 2.5
BIOS features	InsydeH20 Bios
Audio type	On board
Audio codec	Realtek ALC255 with MaxxAudio
Audio features	Stereo speakers
MIL-STD tested	Yes, selected MIL-STD-810G tests passed. MIL-STD-810G test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.
Display	
Display notes	ISO 9241-307 - Pixel class II HD - Viewing angle: Left/Right 45°, Top 20°, Bottom 40°; Color Gammut: 45% FHD - Viewing angle: Left/Right 85°, Top 85°, Bottom 85°; Color Gammut: 72% UHD - Viewing angle: Left/Right 85°, Top 85°, Bottom 85°; Color Gammut: 72%
Graphics	
Base unit	LIFEBOOK U758
TFT resolution (DisplayPort)	up to 4096 × 2160
TFT resolution (HDMI)	up to 1,920 x 1,200
TFT resolution (VGA)	up to 1,920 x 1,200
TFT resolution (DVI on Port Replicator)	up to 1,920 x 1,200
Graphics brand name	Intel® HD Graphics 620
Graphics features	3 Display Support
Graphics notes	Shared memory depending on main memory size and operating system
Interfaces	
DC-in	1
Audio: line-out / headphone	1 (combo port with Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)
Internal microphones	2x digital array microphones (optional) 2x Type-A (1 with Anytime USB charge functionality)
USB 3.1 Gen1 (USB 3.0) total	1x Type-C (with Power Delivery functionality)
USB Type-C	1
VGA	1
DisplayPort	1 (exclusive with HDMI)
HDMI	1 (exclusive with DP)
Ethernet (RJ-45)	1 (with status LED)
Memory card slots	1 microSD up to 2GB, microSDHC up to 32GB, microSDXC up to 128GB Speed Class: up to UHS-I
SmartCard slot	1 (optional)
SIM card slot	1 (only for models with integrated 4G/LTE module)
Port Replicator interfaces (optional)	
DC-in	1 (19V)
Power on switch	1
Audio: headphone	1
Audio: microphone	1

Page 3 / 6 www.fujitsu.com/fts/mobile

USB 3.1 Gen1 (USB 3.0) total	Port Replicator interfaces (optional)	
DisplayPort 2 VGA 1 DVI 1 Elbernet (R)-45) 1 (10110011000) Rensington Lock support (Portep only, Portep option with key lock to secure Portrep & System) Keyboard and pointing devices Keyboard and pointing devices Keyboard and pointing devices Keyboard who touchstick (spill-resistant) #Keyboard wit outhstick #Berklight keyboard w/o touchstick (spill-resistant) Multi posture touchpad with two mouse buttons Saturs (TP Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LIE antennas optional Billuetooth v4.2 WLAN notes Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WMAN Power supply 4C Adapter 19 V 16 S W (3.4.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light: AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light: AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V 760 W A Adapter to usage with system 90 W AC Adapter for usage with Pott Replicator 19 V 760 W AC Adapter for usage with system 90 W AC Adapter for usage with Pott Replicator 19 V 760 W AC Adapter for usage with pott Pott Pott Pott Pott Pott Pott Pott		4x Type-A
Tithemet (RJ-45) 1 (1010011000) Kensington Lock support 1 (Portrep only, Portrep option with key lock to secure Portrep & System) Keyboard and pointing devices Keyboard who touchstick (spill-resistant)#Keyboard w/ touchstick (spill-resistant)#Keyboard w/ touchstick #Backlight keyboard w/o touchstick (spill-resistant)#Keyboard prich 19 mm. Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Setatus ED Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth 42 WLAN notes Import and usage according to country specific regulations. GPS Embedded in 3GAG module if configured with WWNN Power Supply AC Adapter 19 14 / 55 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Sim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Power Ac Adapter end in this propriet of the propriet of th	,	
DVI 1 (101001000) Kersington Lock support (1) (Portrep only, Portrep option with key lock to secure Portrep & System) Keyboard and pointing devices Keyboard and pointing devices Keyboard w/o touchscick (spill-resistant) #Keyboard w/o touchstick Backlight keyboard w/o touchstick (spill-resistant) RKeyboard pitch: 19 mm, Keyboard stucke: 1.7 mm Multit gesture touchpad with two mouse buttons Status LED Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2.LTE antennas optional Bluetooth 4.2 WLAN encryption WFP, WPA, WPA.2 WLAN encryption WFP, WPA, WPA.2 WLAN notes Import and usage acrosting to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power Supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) Bilm and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W (4.7 A), 100 V - 240 W, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter extennology 19 V / 90 W / 40	DisplayPort	2
Exercise (R)-45) 1 (101001000) Kensington Lock support 1 (Portrep only, Portrep option with key lock to secure Portrep & System) Keyboard and pointing devices Keyboard who touchstick (spill-resistant) #Keyboard wit touchstick (spill-resistant) Number of keyboard keys: 106, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Sotus LTD Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth 4-2. WLAN encryption WFP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. CPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 Y / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 15 battery options Lithium polymer battery 4-cell, 50 Wh Lithium polymer battery 4-cell, 50 Wh Battery (rature Quick Charge 080% in 1 h Runtime 1st battery Up to 10 h Battery untime information is based on worldwide acknowledged BAPCo* MobileMark* 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo* MobileMark* Benchmark provides results that enable direct product comparisons between manufactures. It does not upstance any specific battery untime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Weight (185) From 3.79 lbs Weight notes Weight / Environmental Dimensions / Weight / Environmental Dimensi	VGA	1
Kersington Lock support Keyboard and pointing devices Keyboard with touchstick (spill-resistant) #Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Status LED Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth 4.2 WLAN encryption WEP, WPA, WPA2 WLAN encryption WEP, WPA, WPA2 WLAN motes Import and usage according to country-specific regulations. GPS Embedded in 36/4G module if configured with WWAN Power supply AC Adapter 19 V 16 SW (3.4.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) slim and light AC Adapter 19 V 16 SW (3.4.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) Watt AC Adapter rechnology 19 V 19 SW (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter 19 V 18 SW (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter 19 V 18 SW (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter 19 V 18 SW (4.2.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter rechnology 19 V 19 SW (4.7.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC-Adapter Notes 6 59/80/W AC Adapter for usage with system/ 90 W AC Adapter for usage with Port Replicator 1st battery options Lithium polymer battery 4-cell, 50 Wh 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge: 80% in 1 h Runtine 1st battery Quick Charge	DVI	1
Keyboard and pointing devices Keyboard w/o touchstick (spill resistant) Keyboard w/o touchstick (spill resistant) Number of keyboard keys: 106, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi agesture touchpad with two mouse buttons Status IED Power Button Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Buletooth V4.2 WLAN encryption WEP, WPA, WPA.2 WLAN notes Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 V / 65 W (3.4.2 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) slim and light AC Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) AC Adapter (stronology 19 V / 90 W (4.7.4 A), 100 V - 240 V, 50 W - 240 V / 90 W (4.7.4 A), 100 V - 240 V / 90 W	Ethernet (RJ-45)	1 (10/100/1000)
Keyboard wlo touchstuck (spill-resistant) #Keyboard w/r touchstick#Backlight keyboard wlo touchstick (spill-resistant) Number of keyboard keys: 106, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Will agesture touchpad with two mouse buttons Status LED Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth 4, 2 WLAN encryption WEP, WPA, WPA2 WLAN encryption WEP, WPA, WPA2 WLAN encryption Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.72 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V / 80 W (4.72 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 19 V / 80 W (4.72 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W80W AC Adapter for usage with system/ 90W AC Adapter for usage with Port Replicator 1st battery Lithium polymer battery 4-cell 50 Wh 1st battery Lithium polymer battery 4-cell 50 Wh 1st battery Up to 10 h Battery features Ouk Charges 80% in 1 h Runtime 1st battery Up to 10 h Battery for battery 4-cell 50 Wh Battery interest of the second of a diditional details. The BAPC for only product model, configuration, application and power management settings. The battery depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions / Weight may vary depending on actual configuration Operating relative humidity 2 0-80%	Kensington Lock support	1 (Portrep only, Portrep option with key lock to secure Portrep & System)
Number of keyboard keys: 106, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Status LED Power Button Wireless technologies Antennas 2 Dual band WIAN antennas, 2 LTE antennas optional Bluetooth v4.2 WIAN necryption WEP, WPA, WPA2 WIAN notes Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Dewart AC Adapter for usage with Port Replicator 18 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Adapter for usage with Port Replicator 18 battery options Lithium polymer battery 4-cell, 50 Wh 18 battery options Lithium polymer battery 4-cell, 50 Wh 18 battery options Lithium polymer battery 4-cell Battery facults Battery functions Up to 10 h Runtime 1st battery up to 10 h Battery motes Battery runtime information is based on worldwide acknowledged BAPCoff MobileMark® 2014 (office productivity). Refer to www.bapora.com for additional details. The BAPCoff MobileMark® Benchmark provides results that enable direct product comparisons between manufactures. It does not guisarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 3/8 x 256 x 19 2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight notes Weight notes Weight notes Weight notes Weight notes Operating ambient temperature 5 - 35 "C (41 - 95 "T) Operating relative humidity 20 - 80%	Keyboard and pointing devices	
Multi gesture touchpad with two mouse buttons Status LED Power Button Wireless technologies Antennas 2 Dua band WLAN antennas, 2 LTE antennas optional Bluetooth v.4.2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 Y / 65 W (3.42 A), 100 Y - 240 V, 50 Hz - 60 Hz, 3 pin (grounded) slim and light AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Watt AC Adapter technology 15 Y / 90 W (4.72 A), 100 Y - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (as year of the state of SWBDN AC Adapter for usage with system / 90W AC Adapter for usage with Port Replicator Ist battery options Lithium polymer battery 4-cell, 50 Wh Ist battery Lithium polymer battery 4-cell, 50 Wh Ist battery Up to 10 h Battery notes Battery multime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity), Refer to wave bapoc.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufactures. It does not guarantee arry specific battery unitime which actually can be lower and may vary depending on product model, onliquization, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight motes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating ambient temperature 5 - 35 °C (41 - 95 °F)		Keyboard w/o touchstick (spill-resistant)#Keyboard w/ touchstick#Backlight keyboard w/o touchstick (spill-resistant)
Status LED Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth		Number of keyboard keys: 106, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm
Wireless technologies Alternans 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth v4. 2 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) of Watt AC Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W / 8		
Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth		
Antennas 2 Dual band WLAN antennas, 2 LTE antennas optional Bluetooth		Power Bullon
Bluetooth WEP, WPA, WPA2 WEP, W		
WLAN encryption WLAN notes Import and usage according to country-specific regulations. CPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 V / 65 W (3.42.A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology (19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology (19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter technology (19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (19 V / 80 W /		
WLAN notes Import and usage according to country-specific regulations. GPS Embedded in 3G/4G module if configured with WWAN Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter for usage with Port Replicator Ist battery options Lithium polymer battery 4-cell, 50 Wh Ist battery eatures Uithium polymer battery 4-cell, 50 Wh Battery features Uithium polymer battery 4-cell attery active with post of the polymer battery active with polymer battery acti		
Power supply AC Adapter 19 \times / 5 \times (3.42 A), 100 \times - 240 \times, 50 \times / 5.0 \times, 2.5 \times (10 \times, 2.5) \times (10 \tim		
Power supply AC Adapter		
AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W80W AC Adapter for usage with system/ 90W AC Adapter for usage with Port Replicator 1st battery options Lithium polymer battery 4-cell, 50 Wh 1st battery Lithium polymer battery 4-cell Battery features Quick Charge: 80% in 1 h Runtime 1st battery Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Noise emission Please refer to the Eco Declaration Dimensions (Weight / Environmental Dimensions (Wx Dx H) 14.88 x 10.08 x 0.76 (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight notes Weight may vary depending on actual configuration Operating ambient temperature Operating relative humidity 20 - 80 %	GPS 	Embedded in 3G/4G module if configured with WWAN
19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter	Power supply	
Notes 65W/80W AC Adapter for usage with system/ 90W AC Adapter for usage with Port Replicator 1st battery options Lithium polymer battery 4-cell, 50 Wh 1st battery Ethium polymer battery 4-cell Quick Charge: 80% in 1 h Runtime 1st battery up to 10 h Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Noise emission Please refer to the Eco Declaration Dimensions (Wx D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (lbs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product	AC Adapter	19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter
Notes 65W/80W AC Adapter for usage with system/ 90W AC Adapter for usage with Port Replicator 1st battery options Lithium polymer battery 4-cell, 50 Wh 1st battery Lithium polymer battery 4-cell Battery features Quick Charge: 80% in 1 h Runtime 1st battery up to 10 h Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (libs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product		19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology
Lithium polymer battery 4-cell, 50 Wh 1st battery Lithium polymer battery 4-cell Battery features Ouick Charge: 80% in 1 h Runtime 1st battery Battery notes Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (lbs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity Product		19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter
Lithium polymer battery 4-cell Battery features Quick Charge: 80% in 1 h Runtime 1st battery up to 10 h Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight (lbs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product	Notes	65W/80W AC Adapter for usage with system/ 90W AC Adapter for usage with Port Replicator
Battery features Runtime 1st battery Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Noise emission Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity Product	1st battery options	Lithium polymer battery 4-cell, 50 Wh
Runtime 1st battery up to 10 h Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight notes Weight may vary depending on actual configuration Operating ambient temperature 0-7 c 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product	1st battery	Lithium polymer battery 4-cell
Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (Ibs) From 1.72 kg Weight (Ibs) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	Battery features	Quick Charge: 80% in 1 h
Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight (lbs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity Product	Runtime 1st battery	up to 10 h
The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (Ibs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity Product	Battery notes	
manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (lbs) From 3.79 lbs Weight notes Operating ambient temperature Operating relative humidity Product		
depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (lbs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %		
Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (Ibs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product		depending on product model, configuration, application and power management settings. The battery capacity
Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight From 1.72 kg Weight (Ibs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity Product		decreases slightly with every re-charge and over its lifetime.
Dimensions / Weight / Environmental Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	Noise emission	
Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	Noise emission	Please refer to the Eco Declaration
Dimensions (W x D x H) 378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm 14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch Weight (lbs) From 1.72 kg Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	Dimensions / Weight / Environmental	
Weight (lbs) From 3.79 lbs Weight notes Weight may vary depending on actual configuration Operating ambient temperature Operating relative humidity 20 - 80 % Product	Dimensions (W x D x H)	378 x 256 x 19.2mm (non-touch), 19.6mm (touch) mm
Weight (lbs) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product	. ,	14.88 x 10.08 x 0.76 (non-touch), 0.77 (touch) inch
Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product Product	Weight	From 1.72 kg
Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Product ■ 10 mm of the product of the pr	Weight (lbs)	From 3.79 lbs
Operating relative humidity 20 - 80 % Product	Weight notes	Weight may vary depending on actual configuration
Product	Operating ambient temperature	5 - 35 °C (41 - 95 °F)
	Operating relative humidity	20 - 80 %
Compliance link https://sp.ts.fujitsu.com/sites/certificates	Product	
	Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Page 4 / 6 www.fujitsu.com/fts/mobile

Additional Software	
Additional software (preinstalled)	McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Waves MaxxAudio (audio enhancer) Fujitsu Plugfree Network (network management utility) Fujitsu Anytime USB Charge Utility Fujitsu Battery Utility Fujitsu Function Manager Fujitsu DeskUpdate (driver and utility tool)
Additional software (optional)	Microsoft Office (buy license to activate the pre-installed Microsoft Office) CyberLink YouCam (webcam software) Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows®
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 11.6 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)
User Security	Integrated palm vein sensor (optional) Embedded fingerprint sensor (optional) Access protection via internal SmartCard reader (optional) Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)
Warranty	
Warranty Terms & Conditions Product Related Services - the perfect	http://support.ts.fujitsu.com/warranty extension
Recommended Service	X - 9x5, Onsite Response Time: Next Business Day
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Recommended Accessories

Page 5 / 6 www.fujitsu.com/fts/mobile

More information

Fujitsu products, solutions & services

In addition to FUJITSU Notebook LIFEBOOK U758, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Notebook LIFEBOOK U758, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2017-12-20 WW-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH