











American Power Conversion

- •1981 moodustati APC
- •1984 1Ph UPS turuletoomine
- •1990 SmartUPS turuletoomine
- •2007 SE omandab APC



APC by Schneider Electric Baltikumis



Mindaugas Rinkevicius

IT tiimijuht ja andmekeskuste lahendused +370 6872 8372

mindaugas.rinkevicius@se.com

Channel Sales Eliko Jogiste



Eliko Jõgiste IT müügikanali juht Baltikumis +372 5309 4004 eliko.jogiste@se.com Systems & Partners 3-ph Martins Berzins



Martins Berzins IT müügijuht Baltikumis +371 2640 8080 martins.berzins@se.com Inside Sales





Ioana Mitoi Müügitugi + 371 6714 6844 ioana.mitoi@se.com





Reliance on Data Centers is increasing and is driven by these major trends

Digital TRAFFIC

3X Growth of global data center IP traffic over next 5 years

Source: Cisco Cloud Index Report 2015

Internet of THINGS

20.8B connected things by 2020

Source : Gartner, 2010

Data SOVEREIGNITY


Up to 40/0 of total annual turnover can be fined for failing to comply with EU's GDPR by 2018

Source: EU Data Protection Reform

Edge COMPUTING

40% of IoT data will be stored, processed, analyzed and acted upon at the edge

Source: IDC WW IoT Predictions, 2015



The computing ecosystem continues to evolve in order to address limitations of the cloud **CENTRALISED CLOUD LOCAL TELCO EDGE Cloud Services** Content Delivery (5G) Massive compute and storage located in remote areas **LOCAL INDUSTRIAL EDGE** Local Processing Reduce bandwidth needs **IoT REGIONAL EDGE** Content Delivery **Cloud Services** LOCAL COMMERCIAL EDGE Large compute Local Processing and storage Consolidate and prioritise data located in urban **Content Delivery** Smart Function enablement areas Compute and storage where data Schneider Electric is generated and consumed by Schneider Electric

We offer you a complete, easy way to deploy Edge environments


Deployment Standardization and Redundancy

Design and deploy distributed IT infrastructure in a quick, easy, and repeatable way with configuration solutions and selector tools to assist with configurations across all deployment types.




Remote Site Management

Optimize your edge computing sites and prevent the most common causes of downtime by simplifying the monitoring and servicing of your physical infrastructure from the edge to the enterprise.




Secure Environment

Cybersecurity starts with physical security. Protect critical edge computing deployments with montoring, controlling and supervising edge computing sites from physical threats.





Partner Portal – www.apc.com



EcoStruxure IT Expert

EcoStruxure IT Expert is a cloud-based application for real time vendor-neutral device monitoring, trending, and root cause analysis.

Why EcoStruxure™ IT?-

Make IT infrastructure more reliable & efficient while simplifying monitoring by offering complete visibility, alerting & analytics tools for end customers with environments that have qualities such as:

- Distributed IT i.e. local edge & branch locations
- Hybrid IT
- Connected devices that speak SNMP or Modbus TCP

Value to Your Customer

EcoStruxure™ IT allows you to assess and monitor your customer's existing IT environment and give them recommendations on:

- How to decrease utility costs by right-sizing power & cooling configurations
- How your customer compares with other companies with similar IT environments
- How to proactively handle issues and incidents and avoid downtime & interruptions



Instant visibility to critical infrastructure health

Sign up for a free demonstration & 30-day trial of EcoStruxure™ IT Expert

Get Started Today



Võta kaasa!

- EDGE komputing
- EcoStruxure IT- ecostruxureit.com
- Partnerite portaal- www.apc.com



Lithium Ion Smart-UPS On-Line - TCO<53%

Smart-UPS On-Line 2nd Generation UPS

- 1 kVA,1.5 kVA, 2.2kVA, 3kVA 230V UPS
- No internal batteries
- Rack/Tower format
- Same features as the SRT models

Lithium-Ion external battery pack

- 5000 loading cycles (vs. 500 lead batteries)
- Tolerates up to 40C Temperature
- Battery Management System included for advanced battery management and safety
- Extended run time with up to 5 packs
- Hot swappable battery packs (add, remove, or replace)
- Passed all safety tests and regulations

5 years warranty

- Full warranty on electronics and battery pack!
- Expected life time 10yrs









APC Lithium Ion Smart-UPS Online - TCO



- 1. Lithium Ion aku 5000 laadimistsüklit (vs 500 tava plii akudega UPS)
- 2. Li-lon aku kõrgem temperatuuritaluvus kuni 40C
- 3. Li-Ion aku hoideaeg täiskoormusel 20-30min (vs 5-10min tava UPSi sisene plii aku)
- 4. Li-lon akusid võimalik stackida kokku kuni 5tk (max hoideag 2,5t täiskoormusel)
- 5. Li-lon aku kõrgus 1U vs tava stackitava plii UPSi kõrgus 2-3U
- 6. Li-Ion UPSi elektroonika ja akude garantii 5a ja orienteeruv eluaeg ca 10a



Introducing Smart-UPS™ with APC SmartConnect







SmartConnect is an innovative **cloud based monitoring feature** that provides automatic notifications, firmware updates, and advanced support services.

- > Easy **plug & play** setup and discovery
- > Secure, easy to use remote interface
- Proactive, actionable lifecycle notifications and recommendation
- Integrates into leading remote monitoring and management (RMM) platforms
- Firmware updates delivered automatically and advanced support
- https://www.youtube.com/watch?v=aysMKgzEhJ4

Key Elements of Smart UPS with SmartConnect

Hardware, end user & MSP interfaces, cloud infrastructure



- Port included on new Smart-UPS models 3kVA and lower
- Direct connection to cloud
- No gateway required.

Embedded SmartConnect Port



- Simple set-up and registration
- Accessible from any internet connected device
- Pro-active notifications to ensure availability

Convenient Web Portal




User interfaces

- Downloadable plug-ins available for leading RMM platforms
- Discovery agent support
- Preconfigured UPS alerts and notifications

RMM platform plug-ins


APC SmartConnect - UPSi registreerimine

https://smartconnect.apc.com



https://www.youtube.com/watch?v=aysMKgzEhJ4







Welcome to APC[™] SmartConnect



Let's get started!

Watch our introduction video and learn about key features of the APC SmartConnect web portal; including UPS registration and monitoring.

As a first step, you will need to register a SmartConnect enabled APC UPS to your account. Click the button below to begin the register process.

Vajuta -> ⊕ REGISTER YOUR UPS



Select how to register your UPS



QR Code Scan

Scan the QR Code printed on your UPS using a smartphone or tablet.

SCAN QR CODE >



Product Codes

Manually input the Product ID and Product Key printed on your UPS.

INPUT CODES >




RMM Integration


Register with our Kaseya VSA™ or ConnectWise Automate™ RMM integration.

INSTALL INTEGRATION >






















APC SmartConnect - UPS Status.




DOCUMENTS






APC SmartConnect - Dashboard.






APC SmartConnect, Dashboard - Event Logs.





APC SmartConnect. Dashboard - Alert Settings.





Micro Data Center Solutions



SmartBunker Family with environmental monitoring

Your plug & play Micro DC solution
All manufactured, assembled & tested in a Schneider Electric facility

SmartBunker™ SX

Value priced solutions for traditional IT



IT Capacity	18U
UPS	3kW
PDU	16A
Cooling	No
Software	Yes
Fire-	
Detect/Prevent.	No



IT capacity36U
UPS5kW
PDU32A
CoolingNo
SoftwareYes
Fire-
Detect/PreventNo

SmartBunker™ CX

Sound-proof with decorative exterior for office



ITCapacity	1011
UPS	3KVV
PDU	16A
Noise educt18.	5dB
CoolingF	an
SoftwareY	es
Fire-	
Detect/Prevent	Nο



ITCapacity32U
UPS5kW
PDU32A
Noise reduct.18.5dB
CoolingFan
SoftwareYes
Fire-
Detect/PreventNo

SmartBunker™ FX

Secure, insulated, dust-proof, and actively cooled for industry



IT capacity	23U
UPS	5kW
PDU	32A
Cooling	DX
Software	Yes
Fire-	
Detect/Preve	nt No



IT Capacity30U
UPS8kW
PDU32A
Noise Reduct 20dB
CoolingInRow
SoftwareYes
Fire-
Detect/Prevent-Yes



T Capacity	36U
JPS	. 5kW
DU	32A
loiseReduct	20dB
Cooling	InRow
Software	Yes
ire-	
etect/Preven	t-Yes

Micro DC Xpress

24U Micro DC SX MDC24SX3KVAI

Agility
18U IT space
2 x 3kVA UPS
2x Switch Rack PDU
Netbotz monitoring
Shock Packaging



42U Micro DC SX MDC42SX5KVAI

Capacity 36U IT space 2 x 5kVA UPS 4x Switch Rack PDU Netbotz monitoring Shock Packaging



23U Micro DC FX MDC23FX3KVAI

Ruggedized
23U IT space
2 x 3kVA UPS
2x Switch Rack PDU
Cooling unit
Netbotz monitoring
Shock Packaging



Content	Micro DC Xpress SX		Micro DC Xpress FX
SKU	MDC24SX3KVAI	MDC42SX5KVAI	MDC23FX3KVAI
Dimensions (WxDxH) without Shock Packaging	24U NetShelter SX - AR3104SP1 (600mm x 1070mm x 1198mm)	42U NetShelter SX - AR3100SP (600mm x 1070mm x 1991mm)	23U NetShelter FX - AR5023NC (1100mm x 1500mm x 2200mm)
Net Weight	178kg /395 lbs 247 kg/545 lbs with Shock Packaging	278kg/ 615lbs 394 kg/870 lbs with Shock Packaging	551kg/1,215 lbs
Power Protection	2N 3kVA Smart UPS 230V w NMC SRT3000RMXLI-NC	2N 5kVA Smart-UPS 230V w NMC SRT5KRMXLI	2N 3kVA Smart UPS 230V w NMC SRT3000RMXLI-NC
Power Distribution	2 Rack mount, Networked, Switched AP8958	2 Rack mount, Networked, Switched AP8958	2 Rack mount, Networked, Switched AP8958
Cooling	Free Ventilation	Free Ventilation	Top DX Cooling, 3kW
Environmental Monitoring, security	Temperature and Humidity sensor, Rack Access NetBotz 250 – NBACS125	Temperature and Humidity sensor, Rack Access NetBotz 250 – NBACS125	Temperature and Humidity sensor, Rack Access NetBotz 250 – NBACS125

APC Easy UPS 3S

Uus 3 faasiline midmarket lahendusteks UPS, asendab Galaxy 300 alumise otsa:



Single Blok UPS's Redundancy N+1 Output PF 0,8 / 0,9 / 1,0




Small to Medium

Medium to Large

https://www.youtube.com/watch?v=jr1TmllSubE Videokoolitus




APC Easy UPS 3S, jätkub





Ülejäänud vendorid







Enterprise switchid ja meedia konverterid



Tulemüürid, WAF, spam- ja veebi filtrid



SMB switchid, tulemüürid jm võrgutooted



IP telefonid ja IP PBX (cloud) lahendused











USB dongle server lahendused

Enterprise load balancerid, WAF

Räkid, PDU'd

SMB Storage

SMB Wifi lahendused

Küsimused?