

Solution

HPC



Integrates industry-leading computing, network, and storage devices with management software for a comprehensive, professional solution.

RISC-to-IA



Seamlessly migrates mission-critical applications from closed RISC servers to open, reliable x86 servers to sustain customer business development.

SAP HANA Appliance



Combines HANA software with an optimized hardware platform for a powerful in-memory computing system to accelerate ERP, data warehouses, and other critical applications.

Virtualization



Reduces OPEX by consolidating data centers with reference architectures and optimized deployment.

Big Data



Integrates industry-leading software into optimized hardware for real-time batch data processing and increased value.

FusionCube

FusionCube 9000



Ideal for databases and virtualization

- 56 Gbit/s InfiniBand network
- 7,200,000 IOPS per cabinet
- 192 GB/s throughput per cabinet
- 1 TB data rebuild < 15 minutes

FusionCube 6000



Ideal for virtualization and desktop cloud

- 140 VMs per standard virtualization appliance
- 280 VDI users per standard desktop cloud appliance
- Min. 3 server nodes per 4U chassis, integrated delivery, simplified maintenance
- 11-minute initialization, auto hardware discovery, installation wizard
- 256 nodes, expandable online

KunLun

KunLun 9008/9016/9032



- Multiple applications
Databases, in-memory computing, cloud computing, virtualization platforms, and HPC fat nodes are powered by up to 32 E7 v3/v4 series processors and 768 DDR4 DIMMs.
- High stability and reliability
RAS 2.0 technology, PFAE, and hot swap ensure business continuity.
- Leading performance
NC interconnection chips connect 32 processors for speeds topping SPEC CPU2006 and SPEC JBB2015 benchmark performance testing.
- Open ecosystem
Huawei partners with industry giants to build an open, complete industry chain. E2E solutions improve enterprise ROI in IT systems.

TaiShan

Huawei enterprise-level SSDs feature high performance and reliability to eliminate I/O bottlenecks, accelerate database, virtualization, indexing, web, and ServerSAN applications, while reducing TCO.

NVMe SSD Card ES3600C V3



- Half-height, half-length PCIe card, 800 GB to 3.2 TB capacity, 15/16 nm MLC
- Huawei's ASIC SSD controller and NVMeControl technology
- PCIe 3.0 x4 with 3.2 GB/s bandwidth and 800,000 IOPS
- NVMe standard, UEFI bootable
- 3 DWPD for 5 years

NVMe SSD Disk ES3500P V3 / ES3600P V3




- 2.5" disk (U.2), 800 GB to 3.2 TB capacity, 15/16 nm MLC
- Huawei's ASIC SSD controller and NVMeControl technology
- PCIe 3.0 x4 with 3.2 GB/s bandwidth and 800,000 IOPS
- NVMe standard, hot-swappable, UEFI bootable
- 1 or 3 DWPD for 5 years

FusionServer

Rack Servers


RH8100 V3 8U 8P



Ideal for mission-critical applications

- 8 E7-8800 v3/v4 series processors for superior performance
- 192 DIMMs, memory riser hot swap through live memory migration
- 8, 12, or 24 x 2.5" hard disks
- 18 PCIe slots (2 RAID-dedicated)
- FusionPar hard partitioning technology
- 60 RAS features for stable operation in most-demanding environments

RH5885H V3 4U 4P



Ideal for mission-critical applications such as databases, ERP, BI analytics, Big Data, and virtualization

- 4 E7-4800/E7-8800 v3/v4 series processors with 96 cores
- 96 DDR4 DIMMs for 6 TB capacity
- 8 or 23 x 2.5" hard disks
- 17 PCIe slots (1 RAID-dedicated)

RH5885 V3 4U 4P



Ideal for databases, ERP, BI analytics, Big Data, and virtualization

- 4 E7-4800/E7-8800 v3/v4 series processors with 96 cores
- 48 DDR4 DIMMs
- 8 or 23 x 2.5" hard disks
- 8 PCIe slots (1 RAID-dedicated)
- Flexible configuration of hardware (processors, DIMMs, I/O devices, and hard disks)

RH1288 V3 1U 2P

Ideal for compute-intensive, Big Data, virtualization, and web applications

- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 4 x 3.5" or 8 x 2.5" hard disks
- 3 PCIe slots
- 2 miniSSDs (SATADOMs)



RH2288 V3 2U 2P

Ideal for enterprise data center infrastructure, Big Data, virtualization, and web applications

- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 16 x 3.5" or 28 x 2.5" hard disks
- 6 PCIe slots



RH2288H V3 2U 2P

Ideal for enterprise data center infrastructure, Big Data virtualization, and web applications

- 2 E5-2600 v3/v4 series processors with 44 cores
- 24 DDR4 DIMMs
- 16 x 3.5" or 28 x 2.5" hard disks
- 9 PCIe slots
- 2 miniSSDs (SATADOMs)



5288 V3 4U 2P




Ideal for Big Data, cold data storage, video surveillance, and cloud storage

- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 40 x 3.5" hard disks
- 6 PCIe slots

Blade Servers

E9000 12U 8/16/32 nodes



Ideal for enterprise mission-critical applications, carrier NFV, and HPC

- Excellent performance
 - 64 processors, 15.6 Tbit/s midplane bandwidth, 40GE and IB EDR
 - 15 x 2.5" hard disks/6 x 3.5" hard disks/12 NVMe PCIe SSDs (full-width compute nodes)
- Converged architecture
 - Modular design for computing, storage, switching, cooling, and power supply
 - Dynamic expansion of 2- and 4-socket compute nodes
- High energy efficiency
 - Platinum/Titanium PSUs, DEMA, liquid cooling solution, Energy Star certified

CH121 V3 2P

- 2 E5-2600 v3/v4 series processors
- 24 DDR4 DIMMs
- 2 x 2.5" hard disks
- 1 PCIe slot
- 2 mezzanine card slots
- 2 miniSSDs (SATADOMs)



CH140 V3 2 x 2P

Per child node:

- 2 E5-2600 v3/v4 series processors
- 1 x 2.5" hard disk
- 8 DDR4 DIMMs
- 2 shared mezzanine card slots



CH220 V3 2P

- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 2 x 2.5" hard disks
- 6 PCIe slots
- 4 mezzanine card slots



CH222 V3 2P

- 2 E5-2600 v3/v4 series processors
- 24 DDR4 DIMMs
- 15 x 2.5" hard disks
- 1 PCIe slot
- 2 mezzanine card slots
- 2 miniSSDs (SATADOMs)



CH225 V3 2P

- 2 E5-2600 v3/v4 series processors
- 24 DDR4 DIMMs
- 12 x 2.5" NVMe PCIe SSDs + 2 x 2.5" SAS/SATA HDDs or SSDs
- 1 PCIe slot
- 4 mezzanine card slots
- 2 miniSSDs (SATADOMs)



CH226 V3 2P

- 2 E5-2600 v3/v4 series processors
- 24 DDR4 DIMMs
- 6 x 3.5" SAS/SATA HDDs + 2 x 2.5" SAS/SATA HDDs or SSDs
- 1 PCIe slot
- 2 mezzanine card slots



CH242 V3 4P

- 4 E7 v3/v4 series processors
- 32 DDR4 DIMMs
- 8 x 2.5" hard disks
- 2 PCIe slots
- 4 mezzanine card slots



High-Density Servers

XH6800 4U 4/8 nodes

Ideal for IT infrastructure of cloud data centers

- Optimized for diverse workloads
- A wide array of server nodes for different density and performance
- Flexible computing, storage, and I/O device combinations



XH628 V3 2P

- 4 nodes per chassis
- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 12 x 3.5"/2.5" + 2 x optional 2.5" hard disks
- 5 PCIe slots
- 2 miniSSDs (SATADOMs)



XH622 V3 2P

- 4 nodes per chassis
- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 4 x 2.5" hard disks
- 5 PCIe slots
- 2 miniSSDs (SATADOMs)



XH620 V3 2P

- 8 nodes per chassis
- 2 E5-2600 v3/v4 series processors
- 16 DDR4 DIMMs
- 2 or 4 x 2.5" or 2 x 3.5" hard disks
- 3 PCIe slots
- 2 miniSSDs (SATADOMs)

