















PDU Summary

Basic Rack PDU

- ▶ Reliable power distribution
- ▶ Toolless mounting capabilities
- ▶ Horizontal or vertical mounting capabilities

<p>Rack PDU, Basic, ZeroU, 10A 230V, (15)C13 Cord Length (2 meters) C14</p>  <p>1135696 / AP9568</p>	<p>Rack PDU, Basic, ZeroU, 16A 230V, (15)C13 Cord Length (2.5 meters) IEC320</p>  <p>1223880 / AP9572</p>	<p>Rack PDU, Basic, ZeroU, 16A 230V, (10)C13 & (2)C19 Cord Length (2 meters) IEC320</p>  <p>1160812 / AP9559</p>	<p>Rack PDU, Basic, 1U, 16A 230V, (12)C13 Cord Length (2.5 meters) IEC230</p>  <p>1135695 / AP9565</p>
<p>Rack PDU, Basic, 1U, 32A 400V, (6)C19 Cord Length (2.5 meters) IEC309</p>  <p>1756446 / AP7526</p>	<p>Rack PDU, Basic, ZeroU, 16A 230V, (20)C13 & (4)C19 Cord Length (3 meters) IEC320</p>  <p>1135720 / AP7552</p>	<p>Rack PDU, Basic, ZeroU, 16A 400V, (36) C13 & (6) C19 Cord Length (0.9 meters) IEC309</p>  <p>1386123 / AP7557</p>	<p>Rack PDU, Basic, ZeroU, 16A 230V, (20)C13 & (4)C19 Cord Length (3 meters) IEC309</p>  <p>1404571 / AP7554</p>
<p>Rack PDU, Basic, ZeroU, 16A 230V, (20)C13 & (4)C19 Cord Length (0.9 meters) IEC309</p>  <p>1135699 / AP7551</p>	<p>Rack PDU, Basic, ZeroU, 32A 230V, (20)C13 & (4)C19 Cord Length (3 meters) IEC309</p>  <p>1195251 / AP7553</p>	<p>Rack PDU Extender, Basic, 2U 32A, 230V, (4)C19 Cord Length (8.5m) hard 3-wire</p>  <p>1192650 / AP7585</p>	<p>Rack PDU Extender, Basic, 2U 32A, 230V, (4) IEC 309-32 Cord Length (8.5m) hard 3-wire</p>  <p>1192651 / AP7586</p>

Wünschen Sie mehr Informationen?

Kontaktieren Sie uns unter: 041 266 11 11 oder apc-ch@also.com



PDU Summary

Metered Rack PDU

- ▶ Active metering to enable energy optimization and circuit protection
- ▶ User-defined alarm thresholds
- ▶ Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet
- ▶ New AP8000 series include real power monitoring, a temperature/humidity sensor port

Rack PDU, Metered, 1U, 10A
 230V, (8)C13
 Cord Length (2 m) IEC-320 C14



2732280 /
 AP7820B

Rack PDU, Metered, 1U, 16A
 230V, (8)C13
 Cord Length (2.5 m) IEC-320 C20




2732281 /
 AP7821B

Rack PDU, Metered, 2U, 32A
 230V, (12)C13S & (4)C19
 Cord Length (3.7 meters) IEC309



2712616 /
 AP7822B

Rack PDU, Metered, ZeroU, 10A
 230V, (16)C13
 Cord Length (3 meters) IEC320



2732282 /
 AP7850B

Rack PDU 2G, Metered, ZeroU,
 16A, 230V, (18)C13 & (2)C19
 Cord Length (0 meters) IEC320



1610354 /
 AP8858

Rack PDU 2G, Metered, ZeroU,
 16A, 230V, (18)C13 & (2)C19
 Cord Length (3 meters) IEC309



1610355 /
 AP8858EU3

Rack PDU 2G, Metered, ZeroU,
 32A, 230V, (36)C13 & (6)C19
 Length (3 meters) IEC309



1609316 /
 AP8853

Rack PDU 2G, Metered, ZeroU,
 16A, 400V, (36)C13 & (6)C19
 Cord Length (1.8 meter) IEC309




1610356 /
 AP8881

Rack PDU 2G, Metered, ZeroU
 32A, 400V, (30)C13 & (12)C19
 Cord Length (1.8 meter) IEC309



1955445 /
 AP8886

Temperature & Humidity Sensor



1272774 /
 AP9335TH

Temperature Sensor



1347847 /
 AP9335T

Cable Containment Brackets with PDU Mounting Capability NetShelter SX



1487924 /
 AR7710

Wünschen Sie mehr Informationen?

Kontaktieren Sie uns unter: 041 266 11 11 oder apc-ch@also.com



PDU Summary

Metered-by-Outlet Rack PDU

- ▶ **Active metering of individual outlets**
- ▶ Enable energy optimization and circuit protection
- ▶ User-defined alarm thresholds
- ▶ Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet
- ▶ New AP8000 series include real power monitoring, a temperature/humidity sensor port

Rack PDU 2G, Metered-by-Outlet
 32A, 230V, (21) C13 &
 (3) C19 Cord Length (3m) IEC309



2332668 /
 AP8453

Rack PDU 2G, Metered-by-Outlet
 16A, 230V, (21) C13 &
 (3) C19 Cord Length (3m) IEC309



2332669 /
 AP8459EU3

Rack PDU 2G, Metered-by-Outlet
 16A, 230V, (21) C13 &
 (3) C19 Cord Length (3m) IEC320



2332670 /
 AP8459WW

Rack PDU 2G, Metered-by-Outlet
 16A, 400V, (21) C13 & (3) (3) C19
 Cord Len (1.8m) IEC309



2332667 /
 AP8481

Cable Containment Brackets with
 PDU Mounting Capability
 NetShelter SX



1487924 /
 AR7710

Zero U Accessory Mounting
 Bracket NetShelter SX



1699240 /
 AR7711

Temperature & Humidity Sensor



1272774 /
 AP9335TH

Temperature Sensor



1347847 /
 AP9335T

Wünschen Sie mehr Informationen?

Kontaktieren Sie uns unter: 041 266 11 11 oder apc-ch@also.com



PDU Summary

Switched Rack PDU

- ▶ Active metering to enable energy optimization and circuit protection
- ▶ User-defined alarm thresholds
- ▶ Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet
- ▶ New AP8000 series include real power monitoring, a temperature/humidity sensor port
- ▶ **Remote individual on/off switching**

**Rack PDU, Switched, 1U, 10A
 230V, (8)C13
 Cord Length (2 meters) IEC320**



2681890 /
 AP7920B

**Rack PDU, Switched, 1U, 16A
 230V, (8)C13
 Cord Length (2.5 meters) IEC320**



2688705 /
 AP7921B

**Rack PDU, Switched, 2U, 32A
 230V, (16)C13
 Cord Length (3 meters) IEC309**



2732283 /
 AP7922B

**Rack PDU, Switched, ZeroU
 10A, 230V, (16)13
 Cord Length (3 meters) IEC320**



2689712 /
 AP7950B

**Rack PDU 2G, Switched, ZeroU
 16A, 230V, (21)C13 & (3)C19
 Cord Length (3 meters) IEC309**



1627742 /
 AP8959EU3

**Rack PDU 2G, Switched, ZeroU
 16A, 230V, (21)C13 & (3)C19
 Cord Length (0 meters) IEC320**



1627741 /
 AP8959

**Rack PDU 2G, Switched, ZeroU
 32A, 230V, (21)C13 & (3)C19
 Cord Length (3 meters) IEC309**



1627678 /
 AP8953

**Rack PDU 2G, Switched, ZeroU
 16A, 230V, (7)C13 & (1)C19
 Cord Length (3 meters) IEC309**



1627740 /
 AP8958EU3

**Rack PDU 2G, Switched, ZeroU
 16A, 230V, (7)C13 & (1)C19
 Cord Length (0 meters) IEC320**



1627679 /
 AP8958

**Rack PDU 2G, Switched, ZeroU
 16A, 400V, (21)C13 & (3)C19
 Cord Length (1.8 meters) IEC309**



1627743 /
 AP8981

**Rack Bracket Kit, 0U,
 for HP Racks**



not for AP9551, AP9567, AP9568, and
 AP9572

1756445 /
 AP7406

**Cable Containment Brackets with
 PDU Mounting Capability
 NetShelter SX**



1487924 /
 AR7710

Wünschen Sie mehr Informationen?

Kontaktieren Sie uns unter: 041 266 11 11 oder apc-ch@also.com



PDU Summary

Switched Rack PDU - Metered-by-Outlet

- ▶ Individual outlet level power metering and user resettable energy (kWh) logs
- ▶ Individual outlet level control for power cycling remotely located equipment, controlling outlet access (i.e. turn off unused outlets), and user-defined equipment power-up sequencing
- ▶ **Remote individual on/off switching**
- ▶ Active power metering and remote alarming including volts, amps, real power (kW), and energy (kWh) measurements
- ▶ Comprehensive device, phase, and breaker bank level metering for overload protection, capacity planning purposes, and energy efficiency initiatives
- ▶ Fully featured network management connectivity capability via web, SNMP, telnet
- ▶ Environmental temperature and humidity sensor input for active monitoring and alarming via the Rack PDU network device port
- ▶ Redundant internal power supplies provide maximum product reliability
- ▶ Network Port Sharing (Up to 4 rack PDUs share one IP address in one enclosure)

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V (21)C13 & (3)C19, (0m)



1940295 / AP8659

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V (21)C13 & (3)C19, (3m) IEC309



1940296 / AP8659EU3

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V (21)C13 & (3)C19, (3 m) IEC309



1698527 / AP8653

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 400V (21)C13 & (3)C19, (1.8m) IEC309



1940297 / AP8681

Temperature & Humidity Sensor



1272774 / AP9335TH

Temperature Sensor



1347847 / AP9335T

Rack Bracket Kit, 0U, for HP Racks



not for AP9551, AP9567, AP9568, and AP9572

1756445 / AP7406

Cable Containment Brackets with PDU Mounting Capability NetShelter SX



1487924 / AR7710

Wünschen Sie mehr Informationen?

Kontaktieren Sie uns unter: **041 266 11 11** oder apc-ch@also.com