Securepoint RC1000R G6 Security UTM Appliance



Marke : Securepoint

Artikel-Code: SP-UTM-22511

Produktname : RC1000R G6 Security UTM Appliance

RC1000R G6 Security UTM Appliance

Securepoint RC1000R G6 Security UTM Appliance:

Bis maximal 1000 UTM Benutzer - Firewall, VPN-Gateway, zwei Virus-/Malware-Scanner, High-End Spam-Filter, Echtzeit Content-Filter für Web und E-Mail, Zero-Hour-Protection, IDS/IPS, Authentisierung etc. 19" Gerät / 1 HE Redundantes Netzteil (Hotplug) Premium 19" Teleskopschienen 8 x 2,5 GBit LAN Port (RJ45) 2 x 10 GBit SFP Slot (GBit) 1 x HDMI 2 x USB V3 1 x Console Port (RJ45) 2 x Erweiterungsslot AES Hardwarebeschleunigung
Securepoint RC1000R G6 Security UTM Appliance. Firewall-Durchsatz: 59 Gbit/s, HTTP-Proxy-Durchsatz: 3,5 Gbit/s, VPN-Durchsatz: 6,9 Gbit/s. Zahl der Benutzer: 1000 Benutzer. Unterstützte Sicherheitsalgorithmen: AES. Übertragungstechnik: Kabelgebunden, Ethernet LAN Datentransferraten: 2500 Mbit/s, Konsolen-Port: RJ-45. Speichermedien Typ: SSD

Datenübertragung	
Firewall-Durchsatz *	59 Gbit/s
HTTP-Proxy-Durchsatz	3,5 Gbit/s
VPN-Durchsatz	6,9 Gbit/s
Leistungen	
Reset-Knopf	✔
Netzwerk	
Zahl der Benutzer	1000 Benutzer
Sicherheit	
Unterstützte Sicherheitsalgorithmen	AES
Management-Funktionen	
LED-Anzeigen	✔
Anschlüsse und Schnittstellen	
Übertragungstechnik	Kabelgebunden
USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ A	2
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	8
Ethernet LAN Datentransferraten	2500 Mbit/s
Konsolen-Port	RJ-45
Anzahl HDMI-Anschlüsse	1

Anschlüsse und Schnittstellen	
Menge Modul-Steckplätze SFP+	2
Anzahl der Erweiterungsslots	2
Speichermedium	
Speichermedien Typ	SSD
Design	
Rack-Einbau	✔
Formfaktor	1U
Energie	
AC Eingangsspannung	100-240 V
AC Eingangsfrequenz	50/60 Hz
Stromverbrauch (max.)	360 W
Unterstützung für redundantes Netzteil	✔
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-20 - 60 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 80%
Gewicht und Abmessungen	
Breite	430 mm
Tiefe	475 mm
Höhe	44 mm

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-SEP-2025. Prints or copies of Information are only valid on the printed Publication date