Product Specifications

COMMSCOPE®

POWERED BY ANDREW®



245171

Andrew 3M™ Cold Shrink™ Kit for 7/8 in to 1/4 in through 1/2 in connections

Dimensions

Nominal Size	1/2 in | 1/4 in | 7/8 in
Cable Diameter for Seal, maximum	21.34 mm | 0.84 in
Cable Diameter for Seal, minimum	7.37 mm | 0.29 in
Inner Diameter	51.31 mm | 2.02 in
Length	254.00 mm | 10.00 in
Width	53.85 mm | 2.12 in

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	One 1/4 in–1/2 in to 7/8 in
Color	Black
Includes	One EPDM rubber tube | One sealing foam strip
Material Type	EPDM rubber
Package Quantity	1

Mechanical Specifications

UV Resistance Test Method	UV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp
UV Resistance, minimum with no degradation	≥1000 hours
Weather Resistance Test Method	04AS00-03.6.0 | MIL-STD-1344A, Method 1002

Packed Dimensions

Height	30.0 cm | 11.8 in
Length	4.6 cm | 1.8 in
Shipping Weight	0.18 kg | 0.40 lb
Width	7.0 cm | 2.8 in

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
China RoHS SJ/T 11364-2006	Below Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

©2013 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: July 26, 2013